





SITUATION

A water park needed a labor efficient method to restore and maintain gel coat waterslides. Because of labor shortages it was not feasible to continue to manually clean and wax the slides weekly during the season. The company was actively looking for a better way to to maintain and protect their most critical asset.

LOCTITE SOLUTION

A LOCTITE[®] Technical Sales Engineer reviewed the requirements and recommended a total solution. Clean the slide surface with Frekote PMC, then apply LOCTITE[®] PC 4400TM with a HVLP spray gun. LOCTITE[®] PC 4400TM is a clear one-part polyurethane/polyurea hybrid coating. It dries tack-free in an hour. Within 24 hours it forms an extremely hard and high-gloss flexible coating that provides strong corrosion, abrasion, chemical and UV resistance.


BENEFITS

LOCTITE[®] PC 4400TM reduced labor by 75% for the first season. It required less labor for the initial application and no re-application was needed the rest of the season. In addition, LOCTITE[®] PC 4400TM restored the color and gloss of the faded, weathered slides and maintained this high- quality appearance through-out the season. It also protected the gel coat from cracking, a safety risk for users. LOCTITE[®] PC 4400TM is expected to deliver years of protection, a dramatic improvement in performance and reduction in labor.

Product	Size	IDH
LOCTITE [®] PC 4400 [™]	1 liter	2573885
	1 gallon	2573975

Contact Your Local Applied® Service Center 1-877-279-2799


DISCLAIMER: The above content is provided by the supplier. Applied® does not guarantee the accuracy or timeliness of the content. The above content is provided "AS IS", AND ANY AND ALL EXPRESS AND IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS ARE HEREBY EXCLUDED. All warranties, if any, are solely from the supplier.





*Representative images used to maintain customer confidentiality.







Corporate Headquarters 1 Applied Plaza Cleveland, Ohio 44115 Toll Free Phone: 1-877-279-2799 **Applied.com**